

WILMS Dehumidifier KT 65 Eco

Robust design - easy to handle

Product number: 3100165

Top features

- simple operation via only one switch
- Display panel informs about the operating status
- large wheels for easy transport
- robust design for construction site operation
- Rotary piston compressor
- Fully automatic

All special features at a glance

- fully automatic operation
- fast de-icing through hot gas defrosting
- stackable
- Sockets for special accessories such as ext. hygrostat and condensate pump available

Technical details

Typical room size up to	400 m ³
Working range humidity	50-90 % RF
Working range temperature	5-32 °C
Dehumidification capacity	60 Litres/24h (32°C, 80 %
Refrigerant R 454 c	650 g
Supply voltage	230 / 50 V / Hz
Power consumption	1,3 kW
Pre-fuse current consumption	5,9 / 16 A
Air performance	1000 m ³ /h
Water tank capacity	8 Litres
Dimensions (L x W x H)	555 x 570 x 1000 mm
Weight	42 kg
GWP factor	146
CO ² equivalent	0,095 t
Protection class	IP 44
Volume	56 dB (A)

Scope of supply

Mehr erfahren unter







Dust filter, Water box with hose connection, Operating hours counter, Drain hose approx 40cm

Mehr erfahren unter



https://wilms.de/en/